

Roof Reviver (Primerlock)

Product Information

100% Acrylic Primer Sealer used to stabilise concrete roof tile substrates

PRODUCT FEATURES

- 100% Acrylic Emulsion
- Excellent adhesion to concrete and masonry
- Excellent - Recoatable

Colour	White
Appearance When Dry	Clear
Storage Temperature	Minimum 10°C, Maximum 50°C
Shelf Life	18 months
Pack Size	20L

ESTIMATION

Solids Content (By Weight)	27% ± 1
Dry film thickness	50 microns @ 8 m/L undiluted 25 microns @ 8 m/L diluted 1:1
Wet film thickness per coat	110 microns per coat
Theoretical Coverage	6-8 m ² /L

APPLICATION

Concrete Roof Tiles - "Roof Reviver Primerlock" can only be applied once all repairs have been carried out, and that the roof has been thoroughly cleaned by high pressure water blasting. Ensure roof is free from all latence and contaminants.

Apply "Roof Reviver Primerlock" liberally allowing product to soak into tile surface to saturation point until it just starts to run. Avoid excessive runoff down roof and into guttering.

Mixing – Stir thoroughly with a broad paddle to ensure product is fully incorporated.

APPLICATION DETAILS

Maximum Relative Humidity:	75%
Application Temperature Range:	10°C - 35°C
Methods:	Brush, Roller, Spray – Airless spray preferred for roofing application
Cleaning Solvent:	Water
Max. Volume Thinners:	5% (Water)
Nozzle Size:	Airless Spray 19-21 Thou
Fan Angle:	30° - 50°
Nozzle Pressure:	Between 700-1500 psi (May vary due to size of airless machine)

DRYING CHARACTERISTICS

Temperature (deg.C)	10°	20°
Touch dry	2 hours	1 hour
Handle dry	4 hours	2 hours
Full cure	16 hours	8 hours

Overcoating – Where possible allow dry time between coats for a minimum of two hours at 20°C & 50% relative humidity. Overcoat with "Roof Reviver" for premium results.